

ALPHAMAT SF

Powerful outdoor opopa, with raised travel and cover.



Low cost interior for interior quality. Opaque aspect, elevated travel and coverage.

ARATERISTIC PRODUCT

position:	A base of resin in dispersion of water, pigments and selected leaves.
property rights	<ul style="list-style-type: none"> - On the aspect of opacity - Good quality - Good copy - Elevated travel

ARTTERISTIC TECHNICAL

iscosità:	Brookfield 4000 - 7000 cps
volume (density): H:	1.58 ± 0.05 kg / dm ³ 7 - 9
ontenuto solido:	45 ± 2% by volume; 63 ± 2% in peso
drying at 23 ° C / 65% UR:	Secco al tatto: 1 - 2 hours
overlay:	Dopo 3 - 4 hours
color:	Only with Akzo Nobel's tintometric Acomix tintometric system bases W05, M15 and N00
onfezioni:	White: 1l - 2.5l - 5l - 15l; Basi: 1l - 2,5l - 5l - 15l
alore limit UE for the content	Cat. A / a: 30 g / l (2010). This product contains a maximum of 1 g / l of COV
second physics second EN 13300 reference:	G ₃ Opaco ≤ 10 GU 85 °

 spessore del film secco:	E2	50 µm
 ranulometria:	S1 Fine	> 50 ≤ 100 µm
 otere coprente:	Class 2	≥ 98 <99.5% with travel 8 m ² / l ≥
 brasione a umido:	Class 2	5 µm <20 µm after 200 cycles

ambient landscapes
is the application

Temperature: 5 - 30 ° C; Relative humidity: max 85% The application of the product is carried out in ambient conditions that do not have a negative influence at the time of essay compromising the optimal range of aesthetic and performance characteristics.

methods and instruments

A roller, a pennello and airless spray.
Airless application: Ugello 0.46 - 0.53 mm (0.018 - 0.021 polices)
Pressure: 160 - 180 bar ..

illusion

30% in volume with purchase for the roll application; 45% in volume with purchase for the application of the pen; 10 - 20% in volume with purchase for the airless application.
In order to finish finishing more uniformly, especially when applying intense colors and / or brilliant, after having distributed in a uniform way the painting, orient the roller with the help of the height ..

esa

14 - 16 m²/ l per mano.
The journey can vary based on the characteristics of the cargo, porosity and assortment of supports and the supported application system.

ulizia attrezzi

I bought it after the use.

observation

In confezioni ben chiuse, in luogo fresco ed asciutto, al riparo dal gelo e da fonte di calore.

icing

With no other product. Eventual miscellaneous changes in the technical characteristics and the quality of the product.

vvertenze

ALPHAMAT SF applies its perfect support, internships and support services.
Intense and brilliant colors are sensible and can be seen in scissors, are supported by superficial applications as fragments. To view this, please refer to the ALPHA CLEARCOAT MAT transparent transparent finish application.
For the police of the tinteggiate area they recommend the impugment of morbid spug and water mixed with the detergent POLYFILLA PRO S600 in report 5 L of purchase 35 ml of detergent. Avoid using abrasive pads and detergents containing alcohol or solvents of any type.
Operations such as carteggiatura, sabbiatura, rimozione con fiamma, ecc., Dei vecchi strati di pitture, possono generare polveri e / o fumi pericolosi. Work in a ventilated area and necessarily supply the idons with individual protection. For better information regarding the narrow correction, stocking and manipulation of the product, be sure to consult the Scheda di Sicurezza relationship.

APPLICATION SYSTEMS

repair

New intonations with civilian finishes and compasses: Attend the total internship; accurate tracking to remove incoherence; apply as

fondo una mano di IMPREGNANTE ALPHATEX SF diluito al 400% in volume con acqua

Intonations and razors that are irregular may be mistaken:

Uniform the sandbox surface with POLYFILLA PRO E110 or E120 or E200 or ALPHA STUCCO, wait for the total removal and cartridge to eliminate stabbing and stinging eccentricity; apply as a foundation a man of IMPREGNANT ALPHATEX SF diluted to 400% in volume with water

New cartoon:

Stuccare eventual buchi and irregularity with POLYFILLA PRO F120 or F200 or F210; attend the total removal and cartridge removal to eliminate stabbing and stinging eczema; apply as a foundation a mano di IMPREGNANTE ALPHATEX SF diluito al 400% in volume with water

Vecchie pitture lavabili ben anchorate:

Stuccare eventual buchi and irregularity with POLYFILLA PRO F120 or F200 or F210; attend to total evacuation and mapping to eliminate stabbing and stinging eccentricity; isolate the stucco with IMPREGNANT ALPHATEX SF diluted to 400% in volume with water

Vecchie pitture traspiranti ben anchorate:

Stuccare eventual buchi and irregularity with POLYFILLA PRO F120 or F200 or F210; attend to total evacuation and mapping to eliminate stabbing and stinging eccentricity; isolate the stucco with IMPREGNANT ALPHATEX SF diluted to 400% in volume with water.

Vecchie pitture a tempera

Removal of the paint during temperate treatment after averaging preventively unhealthy; uniform the sanding surface with POLYFILLA PRO E110 or E120 or E200 or ALPHA STUCCO, wait for the total removal and cartridge to eliminate stabbing and stinging eccentricity; apply as a foundation a man of IMPREGNANT ALPHATEX SF diluted to 400% in volume with water

initura

Apply two mani of ALPHAMAT SF with an interval of general 3 - 4 hours between one man and the other

ote

All the information contained in this document is purely indicative and reports only some examples of support that do not represent the totality of the situations that may be of interest in practice, as long as it is necessary to intervene in support not indicated or we will need to return to contact il ns. Technical Assistance Service. In addition, for the correct preparation of supports and the application of valgus products the rule of the post of art rule, which is reported in the frame of Sikkens "The preparation of support in wall", which we invite to consult.

CAPITOLATO VOCES

Dissertation of insertion to capitoli of appeal and prevention

Substantial washable resin based on resin in water dispersion, bark and selected pigments (Tipo ALPHAMAT SF)

CHARACTERISTIC TECHNICAL

Viscosity:

Brookfield 4000 - 7000 cps

Bulk mass (density): Solid

1.58 ± 0.05 kg / dm³

content:

45 ± 2% by volume; 63 ± 2% in peso

Essication at 23 ° C / 65% OF US

Secco al tatto: 1 - 2 hours

Application:

Dopo 3 - 4 hours

Coloration:

Only with Akzo Nobel's tintometric Acomix tintometric system bases W05, M15 and N00

Confessions:

White: 1l - 2.5l - 5l - 15l; Basi: 1l - 2,5l - 5l - 15l

UE value limit for the COV content:

Cat. A / a: 30 g / l (2010). This product contains a maximum of 1 g / l of COV

Second physical value EN

13300 Brilliant:

G₃Opaco ≤ 10 GU 85 ° E

Secco movie viewer:

≥ 50 ≤ 100 μm

RTICOLI

onfezioni

1L - 2.5L - 5L - 15L

color availability

White and inkable with colorimetric machine system

Rative Paints

NO)



is based on years of practical experience and research conducted in our laboratories. We guarantee that the quality of the work is carried out with our reviews by Akzo Nobel Coatings SpA, provided that all the impartial works have been corrected correctly and the work is in good condition. In this case, the final result is negatively influenced by the state of the independence of our will, both of us and of those who have declined. rodotti consignati sono adatti per l'uso previsto. We reserve the right to modify the content of this document without prior notice. your technical schedule will be available, this one will not be valid.