

LIGNEX® GARTENHOLZBODEN ÖL

Oil for the care of wooden floors outdoors

3260-b January 2016

Description

Product: LIGNEX GARTEN HOLZBODEN ÖL is a biocide-free protective oil based on natural oils in a solvent free of aromatic composites. Ideal for the care of wooden floors placed outdoors, such as terraces, patios, walkways, etc.

Fields of use: for the care of hardwood floors, placed outdoors but not in the ground and / or fresh water.

Protection: LIGNEX GARTEN HOLZBODEN ÖL penetrates deeply into the wood, is highly water repellent, highlights the structure of the wood and, if used regularly, prevents the wood from graying.

Tints: yellowish

Packs: 0.75 LT - 2.5 L - metal milk

Technical data

Density: ca. 0.85 g / cm³ (+ 20 ° C) **Viscosity:**
approx. 60 sec / DIN cup, 2 mm at +20 ° C **Flash**

point: 61 °C

Drying: depending on the type of wood, the quantity applied and the weather conditions, the product is dry after about 8-12 hours. High atmospheric humidity and / or low temperatures slow down the drying time.

Odor: own faint smell; odorless after drying.

Storage: 5 years in intact packaging. Keep cool, but protected from frost. Close partially used jars well; if the bladder is excessively large, transfer to smaller containers.

Store away from food, drink and feed. Only store the original packaging intact and out of the reach of children.

Application Notes

General indications: mix well before and during use.

Application system: fits perfectly. Apply LIGNEX GARTEN HOLZBODEN ÖL liberally with a brush and let it penetrate into the wood. Remove excess product with a cloth after approx. 10 minutes.

Application temperature: 5 - 35 ° C

Preparation of the substrate : the wood to be treated must be dry and free from dust and grease. Do not apply on wood with humidity higher than 18%. Eliminate old paints that are not well anchored. Clean any resinous areas or pockets on the surface with nitro thinner.

Application tips: On end grain it is necessary to increase the number of coats of LIGNEX GARTEN HOLZBODEN ÖL to reduce water absorption as much as possible.

Recommended cycles:

- New wood on the outside	Apply LIGNEX GARTEN HOLZBODEN ÖL several times at intervals of at least 8 hours. After each application, remove the excess product with a cloth after approx. 10 minutes.
- Renewal outside	Remove old paint that is not well adherent; clean and sand the surface to improve adhesion. Then apply LIGNEX GARTEN HOLZBODEN ÖL and remove the excess product with a cloth after approx. 10 minutes. It is possible to apply several times at intervals of at least 8 hours depending on the absorption of the wood On surfaces particularly gray with age, first use Lignex Garten Aufheller. Read the technical instructions carefully before use.

LIGNEX[®] GARTENHOLZBODEN ÖL
Oil for the care of wooden floors outdoors

3260-b January 2016

Caution: cloths impregnated with LIGNEX GARTEN HOLZBODEN ÖL must be placed carefully in a tightly closed, non-flammable, airtight container to be disposed of at a special waste collection center. Danger of self-ignition.

Surrender: approximately 22 m² per liter per application (depending on the absorbency of the wood and the amount of application).

Dilution: LIGNEX GARTEN HOLZBODEN ÖL is ready for use. It must not be diluted.

Overpaintable: under normal conditions, after approx. 8 hours.

Cleaning of tools : with white spirit or nitro thinner, immediately after use.

Special instructions

Always observe the usual precautions for painting works and follow the instructions given in the safety data sheet. Keep out of reach of children. During application, protect your face, hands and eyes and ensure sufficient ventilation. Do not inhale the vapors / aerosols. Repeated exposure can cause skin dryness and cracking. Avoid working near open flames or sparks. If swallowed, seek medical attention immediately and show him the container or label. After application, wash your face and hands thoroughly with water and a suitable detergent.

Prevent the product from polluting water courses and waste water or from penetrating into the ground.

European waste catalog: 08 01 11 waste paint and varnish containing organic solvents or other dangerous substances. **Water hazard class:** WGK 1, (Self-classification): not very dangerous.

Classification according to VbF: A III.

ADR / RID: Not applicable

The aforementioned indications correspond to the most recent state of the art in development and use. Since the use and application of the products are beyond our sphere of influence, we are only liable for the consistent quality of the products. If in doubt, please ask for our technical advice.