



**COLORIFICIO CASATI S.p.A.**  
via Valpantena, 59/B  
37142 Poiano · Verona, Italia  
t +39 045 550 244 · f +39 045 550 884  
w casati.it · e casati@casati.it  
Cod. Fisc./ P. IVA 00222520231

## SCHEDA TECNICA

(Cod. 527101)

### HYDROBASE

Water based primer (Veronite all 'water) sandable based on special acrylic resins.



#### PRODUCT DESCRIPTION

<b>FIELD OF APPLICATION</b>	It is particularly suitable for indoor applications, on sandable wood.
<b>COLOR</b>	White.
<b>SPECIFIC WEIGHT</b>	1.50 Kg / L
<b>BRILLIANCE</b>	Opaque.
<b>BINDER</b>	Acrylic.
<b>DRY</b>	60 ± 5%
<b>VISCOSITY F8</b>	27sec. ± 3
<b>SUBSTANCES CONTAINED</b>	Precious acrylic resins in emulsion, fillers and various additives.

#### PROCESSING

<b>APPLICATION METHOD</b>	<p>The substrate must be healthy, clean, dry, free from traces of dirt, grease, etc....</p> <p>Where there are dust, grease spots or patinas, sand the substrate before application and use suitable degreasing solvents.</p> <p>On previously painted woods proceed with mechanical removal, sandblasting or paint stripping.</p> <p>Depending on the method of application, the product can be diluted up to a MAX of 15% of water by volume. It is advisable to mix thoroughly and apply in the direction of the wood grain.</p> <p>After 2 hours from application at 20 ° C and relative humidity below 50%, it already allows excellent sanding.</p> <p>This base coat makes it possible to isolate the wooden support before applying the finishing product, which can be water-based (BRILLANTE, ...) or solvent-based (SEA GULL, ...).</p>
<b>DRYING</b>	Depending on the temperature, 1 hour dust free, 12 hours deep.
<b>SANDABILITY</b>	Sandable after 2 hours at 20 ° C and relative humidity below 50%. It reaches maximum sanding after 12 hours.
<b>TOOLS</b>	The product can be applied by brush, roller or spray.
<b>WORKING TEMPERATURE</b>	It is not recommended to apply HYDROBASE at temperatures below 5 ° C, above 35 ° C and with relative humidity > 70-75% in order to avoid drying delays and non-hardening of the film.
<b>CONSUMPTION</b>	About 10 sqm / l per coat (varies according to the absorption of the substrate).
<b>DILUTION</b>	Dilute with water in the ratio of 5-15%.
<b>CLEANING THE TOOLS</b>	Immediately after use with water.
<b>STORAGE</b>	<p>Store in a cool, dry place.</p> <p>If these conditions are respected, the stability of the unopened package is guaranteed for 24 months.</p>

<b>INFORMATION</b>	
<b>COV</b>	Interior / exterior finishing and cladding paints for wood, metal or plastic: EU limit value for this product: 130 g / L. This product contains a maximum of <30g / L of VOC.
<b>SAFETY TIPS</b>	For information on the correct disposal, storage and handling of the product, please consult the relevant Safety Data Sheet.
<b>DISPOSAL</b>	Only hand in containers emptied of residues for recycling. Completely dried material residues can be disposed of as household waste.  Milk with liquid residues can be disposed of at local collection centers for special waste.

The information contained in this product information has been prepared in accordance with the best of science and is in accordance with the current state of the art. However, they must be considered non-binding, as the different properties of the substrate, the processing method and the application are beyond our possibilities of intervention. Special cases due to the particular properties of the building must be observed. Legal constraints cannot be inferred from the above indications.