

Colorificio A. & B. Casati SpARevision n.9
Revision date 30/10/2015
Printed on 03/11/2015
Page no. 1/7

IT

527000 - TRANSPARENT HYDROBASE**Safety Data Sheet****SECTION 1. Identification of the substance / mixture and of the company / undertaking****1.1. Product identifier**Code: 527000
Name: TRANSPARENT HYDROBASE**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Description / Use: Turapori to the water.

1.3. Information on the supplier of the safety data sheet

Business name: Colorificio A. & B. Casati SpA Via
Address: Valpantena 59 / B - Poiano
Location and State: 37142 VERONA (VR)
ITALY
tel. 045 550 244
fax 045 550 414

e-mail of the competent person responsible for the safety data sheet: tintotec@casati.it

1.4. Emergency telephone number

For urgent information contact: 045550244

SECTION 2. Hazards identification.**2.1. Substance or mixture classification.**

The product is not classified as dangerous according to the provisions of Regulation (EC) 1272/2008 (CLP). However, since the product contains dangerous substances in such a concentration as to be declared in section 3, it requires a safety data sheet with adequate information, in compliance with Regulation (EC) 1907/2006 and subsequent amendments.

Hazard classification and indications: - -

2.2. Label elements.

Danger labeling pursuant to Regulation (EC) 1272/2008 (CLP) and subsequent amendments and adjustments.

Hazard pictograms: - -

Warnings: - -

Hazard statements:
EUH210 Safety data sheet available on request.

Precautionary advice: - -

2.3. Other dangers.

On the basis of available data, the product does not contain PBT or vPvB substances in percentage greater than 0.1%.

SECTION 3. Composition / information on ingredients.**3.1. Substances.**

Not relevant information.

527000 - TRANSPARENT HYDROBASE**SECTION 3. Composition / information on ingredients.**

... / >>

3.2. Blends.**Contains:****Identification. Conc.% Classification 1272/2008 (CLP).****2-BUTOXYETHANOL**

CAS. 111-76-2 1.5 - 2 Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315

THERE IS. 203-905-0

INDEX. 603-014-00-0

Reg. No. 01-2119475108-36

Note: Upper value of the range excluded.

The full wording of the hazard statements (H) is given in section 16 of the sheet.

SECTION 4. First aid measures.**4.1. Description of first aid measures.**

EYES: Remove any contact lenses. Wash immediately and abundantly with water for at least 30/60 minutes, opening the eyelids well. Consult a physician immediately.

SKIN: Take off contaminated clothing. Take a shower immediately. Consult a physician immediately.

INGESTION: Give as much water to drink as possible. Consult a physician immediately. Do not induce vomiting unless expressly authorized by your doctor.

INHALATION: Call a doctor immediately. Take the person out into the fresh air, away from the scene of the accident. If breathing stops, give artificial respiration. Take adequate precautions for the rescuer.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects due to the substances contained, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed. Information not available.**SECTION 5. Firefighting measures.****5.1. Fire fighting.** SUITABLE

EXTINGUISHING MEDIA

The extinguishing media are: carbon dioxide and chemical powder. For product leaks and spills that have not caught fire, water spray can be used to disperse flammable vapors and protect those involved in stopping the leak. UNSUITABLE EXTINGUISHING MEDIA

Do not use water jets.

Water is not effective to extinguish the fire however it can be used to cool closed containers exposed to the flame, preventing bursts and explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

The product, if involved in large quantities in a fire, can considerably aggravate it. Avoid breathing combustion products.

5.3. Recommendations for firefighters. GENERAL INFORMATION

In case of fire, immediately cool the containers to avoid the danger of explosions (product decomposition, overpressure) and the development of substances potentially dangerous for health. Always wear full fire protection equipment. If possible without risk, remove the containers containing the product from the fire.

EQUIPMENT

Normal clothing for firefighting, such as an open circuit compressed air breathing apparatus (EN 137), flame retardant suit (EN469), flame retardant gloves (EN 659) and fire brigade boots (HO A29 or A30).

SECTION 6. Accidental release measures.**6.1. Personal precautions, protective equipment and emergency procedures.** Stop the leak if there is no danger.

Wear suitable protective equipment (including personal protective equipment referred to in section 8 of the safety data sheet) to prevent contamination of skin, eyes and personal clothing. These indications are valid both for the workers and for emergency interventions.

6.2. Environmental precautions.

Prevent the product from entering sewers, surface water, groundwater.

527000 - TRANSPARENT HYDROBASE**SECTION 6. Accidental release measures.**

.../ >>

6.3. Methods and materials for containment and cleaning up.

Suck up the leaked product into a suitable container. Evaluate the compatibility of the container to be used with the product, checking section 10. Absorb the remainder with inert absorbent material.

Provide sufficient ventilation of the place affected by the leak. Check for any incompatibilities for the container material in section 7. The disposal of contaminated material must be carried out in accordance with the provisions of point 13.

6.4. Reference to other sections.

Any information regarding personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.**7.1. Precautions for Safe Handling.**

Ensure an adequate earthing system for plants and people. Avoid contact with eyes and skin. Do not inhale any dusts or vapors or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid the dispersion of the product in the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Keep only in the original container. Store in a ventilated place, away from sources of ignition. Keep containers tightly closed. Keep the product in clearly labeled containers. Avoid overheating. Avoid violent shocks. Keep containers away from any incompatible materials, checking section 10.

7.3. Specific end uses.

Information not available.

SECTION 8. Exposure controls / personal protection.**8.1. Control parameters.**

Normative requirements:

GRB	United Kingdom	EH40 / 2005 Workplace exposure limits
ITA	Italy	Legislative Decree 9 April 2008, n.81
EU	OEL EU	Directive 2009/161 / EU; Directive 2006/15 / EC; Directive 2004/37 / EC; Directive 2000/39 / EC.
	TLV-ACGIH	ACGIH 2014

2-BUTOXYETHANOL**Threshold limit value.**

Guy	State	TWA / 8h		STEL / 15min		
		mg / m ³	ppm	mg / m ³	ppm	
WEL	GRB	123	25	246	50	LEATHER.
TLV	ITA	98	20	246	50	LEATHER.
OEL	EU	98	20	246	50	LEATHER.
TLV-ACGIH		97	20			

Legend:

(C) = CEILING; INALAB = Inhalable Fraction; RESPIR = Breathing Fraction; TORAC = Thoracic Fraction.

8.2. Exposure controls.

Observe the usual safety measures when handling chemicals. HAND PROTECTION

Unnecessary.

SKIN PROTECTION

Unnecessary.

EYE PROTECTION

Unnecessary.

RESPIRATORY PROTECTION

Not necessary, unless otherwise indicated in the chemical risk assessment.

ENVIRONMENTAL EXPOSURE CONTROLS.

Emissions from manufacturing processes, including those from ventilation equipment should be controlled for compliance with environmental protection legislation.

527000 - TRANSPARENT HYDROBASE**SECTION 9. Physical and chemical properties.****9.1. Information on basic physical and chemical properties.**

Physical state	liquid
Color	transparent
Odor	characteristic
Odor threshold.	Unavailable.
pH.	Unavailable.
Melting or freezing point. Initial boiling point.	Unavailable.
Boiling range. Flash point.	Unavailable.
Evaporation rate	> 60 ° C.
Flammability of solids and gases Lower flammability limit.	Unavailable.
Upper flammability limit. Lower explosive limit. Upper explosive limit. Vapor pressure.	Unavailable.
Vapor density	Unavailable.
Relative density.	1.010 Kg / l
Solubility	Miscible with water
Partition coefficient: n-octanol / water: Auto-ignition temperature.	Unavailable.
Decomposition temperature.	Unavailable.
Viscosity	Unavailable.
Explosive properties	Unavailable.
Oxidizing properties	Unavailable.

9.2. Other information. VOC

(Directive 2004/42 / EC): VOC	2.11%	-	21.29	g / liter.
(volatile carbon):	1.28%	-	12.91	g / liter.

SECTION 10. Stability and reactivity.**10.1. Reactivity.**

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL: decomposes under the effect of heat.

10.2. Chemical stability.

The product is stable under normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

In normal conditions of use and storage no dangerous reactions are foreseeable.

2-BUTOXYETHANOL: can react dangerously with: aluminum, oxidizing agents. Forms peroxides with air.

10.4. Conditions to avoid.

None in particular. However, follow the usual precautions towards chemicals.

2-BUTOXYETHANOL: avoid exposure to heat sources and naked flames.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products. 2-

BUTOXYETHANOL: hydrogen.

SECTION 11. Toxicological information.**11.1. Information on toxicological effects.**

In the absence of experimental toxicological data on the product itself, any health hazards of the product have been assessed on the basis of the properties of the substances contained, according to the criteria established by the reference legislation for classification. Therefore, consider the concentration of the individual dangerous substances possibly mentioned in sect. 3, to evaluate the toxicological effects deriving from exposure to the product.

527000 - TRANSPARENT HYDROBASE**SECTION 11. Toxicological information.... / >>****2-BUTOXYETHANOL**

LD50 (Oral).	615 mg / kg Rat
LD50 (Dermal).	405 mg / kg Rabbit
LC50 (Inhalation).	2.2 mg / l / 4h Rat

SECTION 12. Ecological information.

Use according to good working practices, avoiding to disperse the product in the environment. Notify the competent authorities if the product has reached water courses or if it has contaminated the soil or vegetation.

12.1. Toxicity.

Information not available.

12.2. Persistence and degradability.**2-BUTOXYETHANOL**

Solubility in water. mg / l 1000 - 10000
Quickly biodegradable.

12.3. Bioaccumulation potential.**2-BUTOXYETHANOL**

Partition coefficient: n-octanol / water. 0.81

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain PBT or vPvB substances in percentage greater than 0.1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.**13.1. Waste treatment methods.**

Reuse if possible. The residues of the product as such are to be considered special non-hazardous waste.
Disposal must be entrusted to an authorized waste management company, in compliance with national and possibly local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be sent for recovery or disposal in compliance with national waste management regulations.

SECTION 14. Transport information.**14.1. UN number.**

Not applicable.

14.2. UN proper shipping name.

Not applicable.

14.3. Transport hazard classes.

Not applicable.

14.4. Packing group.

Not applicable.

14.5. Dangers for the environment.

Not applicable.

527000 - TRANSPARENT HYDROBASE**SECTION 14. Transport information.... / >>****14.6. Special precautions for users.**

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code.

Not relevant information.

SECTION 15. Regulatory information.**15.1. Standards and legislation on health, safety and environment specific for the substance or mixture.**

Seveso category. None.

Restrictions relating to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006.
None.

Substances in the Candidate List (Art. 59 REACH).

None.

Substances subject to authorization (Annex XIV REACH).

None.

Substances subject to export notification obligation Reg. (EC) 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Sanitary checks.

Information not available.

VOC (Directive 2004/42 / EC):

Interior / exterior finishing and cladding paints for wood, metal or plastic. VOC expressed in g / liter of ready-to-use product:

Maximum limit:	130.00 (2010)
VOC of the product:	20.28
- Diluted with:	5.00% WATER

15.2. Chemical safety assessment.

A chemical safety assessment has not been developed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in sections 2-3 of the sheet:

Acute Tox. 4	Acute toxicity, category 4
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European agreement for the transport of dangerous goods by road
- CAS NUMBER: Number of the Chemical Abstract Service
- EC50: Concentration that gives effect to 50% of the population subject to testing
- CE NUMBER: Identification number in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived no effect level

527000 - TRANSPARENT HYDROBASE**SECTION 16. Other information.... / >>**

- EmS: Emergency Schedule
- GHS: Globally Harmonized System for Classification and Labeling of Chemicals
- IATA DGR: Regulations for the transport of dangerous goods of the International Air Transport Association
- IC50: Concentration of immobilization of 50% of the population subject to testing
- IMDG: International maritime code for the transport of dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identification number in Annex VI of the CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal Dose 50%
- OEL: Occupational exposure level
- PBT: Persistent, bioaccumulating and toxic according to REACH
- PEC: Predicted environmental concentration
- PEL: Predictable level of exposure
- PNEC: Predicted No Effect Concentration
- REACH: EC Regulation 1907/2006
- RID: Regulations for the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration which must not be exceeded during any moment of occupational exposure.
- TWA STEL: Short term exposure limit
- TWA: Weighted average exposure limit
- VOC: Volatile organic compound
- vPvB: Very persistent and very bioaccumulating according to REACH
- WGK: Water hazard class (Germany).

GENERAL BIBLIOGRAPHY:

1. Regulation (EU) 1907/2006 of the European Parliament (REACH)
 2. Regulation (EU) 1272/2008 of the European Parliament (CLP)
 3. Regulation (EU) 790/2009 of the European Parliament (I Atp. CLP)
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 of the European Parliament (II Atp. CLP)
 6. Regulation (EU) 618/2012 of the European Parliament (III Atp. CLP)
 7. Regulation (EU) 487/2013 of the European Parliament (IV Atp. CLP)
 8. Regulation (EU) 944/2013 of the European Parliament (V Atp. CLP)
 9. Regulation (EU) 605/2014 of the European Parliament (VI Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - NI Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - ECHA Agency website

Note for the user:

The information contained in this sheet is based on the knowledge available to us at the date of the latest version. The user must ensure the suitability and completeness of the information in relation to the specific use of the product.

This document should not be construed as a guarantee of any specific property of the product.

Since the use of the product does not fall under our direct control, the user is obliged to observe the laws and regulations in force on hygiene and safety under his own responsibility. No responsibility is assumed for improper use.

Provide adequate training to personnel assigned to the use of chemical products.

Changes from the previous revision. Changes have been made to the following sections:
02/08/09/11/12/14/16.