



TECHNICAL DATA SHEET

TDS 04.026

Product

CEBOIRON CROMO

Description

CEBOIRON CROMO is a water based, acrylic finish for interiors, with pearly and chromium-plated pigments.

CEBOIRON CROMO is available in 1 litre and 2.5 litres containers.

Surface treatment of the substrate

CEBOIRON CROMO must be applied on surfaces which have been previously painted with CEBOSTONE..

SAND and RAIN effect: see CEBOSTONE Technical Data Sheet

Colouring

CEBOIRON CROMO can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

Application

SAND Effect: Over the dry coat of CEBOSTONE, apply one coat of CEBOIRON CROMO with CeboSi paint brush (code A/27) with crossed brush-strokes avoiding clear-cut squaring and overlapping of product.
Refer to the relative Colour Card to choose the colour combination and for full description of the application cycle.

RAIN Effect: Over the dry coat of CEBOSTONE, apply one coat of CEBOIRON CROMO with CeboSi paint brush (code A/27) with regular brush-strokes to follow the direction of the previous application.
Refer to the relative Colour Card to choose the colour combination and for full description of the application cycle.

Useful suggestions

In order to achieve a more uniform and more chromium-plated effect, it is advisable to apply CEBOIRON CROMO in two coats, being careful to wait for the complete drying of the first coat (4-6 hours)

VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)
Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.
CEBOIRON CROMO contains: 80 g/l VOC

Technical characteristics

Estimated Coverage: 6 - 8 m²/litre
Appearance: dense liquid
Specific weight: 1.06 g/cm³
pH: 8.5 – 9
Resistance to washing: The product withstands ordinary cleaning maintenance.
Drying time: 4-6 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOIRON CROMO does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.