

 Cebos Color Srl 24040 Osio Sopra (BG) Via dei Dossi, 7 Tel. +39 035 265141 Fax +39 035 2651431 C.F. & P.Iva 02567630161 info@cebos.it www.ceboscolor.it	Cebos Color Srl	Revision n. 6
	SS 04.015 - CeboStone	Revision date 11/05/2018 Printed on 05/21/2018 Page no. 1/12

Safety Data Sheet

SECTION 1. Identification of the substance / mixture and of the company / undertaking

1.1. Product identifier Code:

SS 04.015

Name

CeboStone

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description / Use Decorative wall finish based on acrylic resin for interiors and exteriors.

1.3. Information on the supplier of the safety data sheet Business

name Cebos Color Srl
 Address Via Dei Dossi n. 7 24040
 Location and State OSIO SOPRA (BG) ITALY

tel. (+39) 035 265141

fax (+39) 035 2651431

e-mail of the competent person,

responsible for the safety data sheet

Responsible for placing on the market:

carlo@cebos.it

Cebos Color Srl

1.4. Emergency telephone number For urgent information contact

Poison Control Centers (CAV): Milan Tel. (+39) 02 66101029; Rome Tel. (+39) 06 3054343;
 Naples Tel. (+39) 081 7472870; Catania Tel. (+39) 095 7594120.
 Technical information: Cebos Color Tel. (+39) 035 265141 (Mon-Fri 8.30 / 12.30 -
 13.30 / 18.00)

SECTION 2. Hazards identification

2.1. Substance or mixture classification

The product is not classified as dangerous according to the provisions of Regulation (EC) 1272/2008 (CLP).

However, since the product contains dangerous substances in a concentration such as to be declared in section 3, it requires a safety data sheet with adequate information, in compliance with Regulation (EU) 2015/830.

Hazard classification and indications:

2.2. Label elements

Danger labeling pursuant to Regulation (EC) 1272/2008 (CLP) and subsequent amendments and adjustments.

Hazard pictograms: - -

Warnings: - -

Hazard statements:

SS 04.015 - CeboStone

EUH210
EUH208

Safety data sheet available on request.
Contains ; Reaction mass of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7]; 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1), 1,2-Benzoisothiazol-3 (2H) -one, 2-octyl-2H-isothiazol-3-one
It can cause an allergic reaction.

Precautionary advice:

--

2.3. Other dangers

On the basis of available data, the product does not contain PBT or vPvB substances in percentage greater than 0.1%.

SECTION 3. Composition / information on ingredients

3.1. Substances

Not relevant information

3.2. Blends

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
QUARTZ		
CAS 14808-60-7	$1 \leq x < 1.5$	STOT RE 2 H373
INDEX 238-878-4		
1,2-Benzoisothiazol-3 (2H) -one		
CAS 2634-33-5	$0 \leq x < 0.05$	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M = 1
INDEX 220-120-9		
INDEX 613-088-00-6		
2-octyl-2H-isothiazol-3-one		
CAS 26530-20-1	$0 \leq x < 0.05$	Acute Tox. 3 H311, Acute Tox. 3 H331, Acute Tox. 4 H302, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M = 1, Aquatic Chronic 1 H410 M = 1
INDEX 247-761-7		
INDEX 613-112-00-5		
Reaction mass of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7]; 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1)		
CAS 55965-84-9	$0 \leq x < 0.0015$	Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M = 1, Aquatic Chronic 1 H410 M = 1
INDEX 613-167-00-5		

The full wording of the hazard statements (H) is given in section 16 of the sheet.

 Cebos Color Srl 24040 Orio Sopra (BG) Via dei Dossi, 7 Tel. +39 035 265141 Fax +39 035 2651431 C.F. & P.Iva 02567630161 info@cebos.it www.ceboscolor.it	Cebos Color Srl	Revision n. 6 Revision date 11/05/2018 Printed on 05/21/2018 Page no. 3/12
	SS 04.015 - CeboStone	

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove any contact lenses. Wash immediately and abundantly with water for at least 30/60 minutes, opening the eyelids well. Consult a physician immediately.

SKIN: Take off contaminated clothing. Take a shower immediately. Consult a physician immediately.

INGESTION: Give as much water to drink as possible. Consult a physician immediately. Do not induce vomiting unless expressly authorized by your doctor.

INHALATION: Call a doctor immediately. Take the person out into the fresh air, away from the scene of the accident. If breathing stops, give artificial respiration. Take adequate precautions for the rescuer.

4.2. Most important symptoms and effects, both acute and delayed

No specific information on symptoms and effects caused by the product is known.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Fire fighting

SUITABLE EXTINGUISHING MEDIA

The extinguishing media are the traditional ones: carbon dioxide, foam, powder and nebulized water.

UNSUITABLE EXTINGUISHING MEDIA

No one in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Avoid breathing combustion products.

5.3. Recommendations for firefighters

GENERAL INFORMATION

Cool the containers with jets of water to avoid product decomposition and the development of substances potentially hazardous to health. Always wear full fire protection equipment. Collect the extinguishing water which must not be discharged into the sewers. Dispose of the contaminated water used for extinguishing and the residue of the fire according to current regulations.

EQUIPMENT

Normal clothing for firefighting, such as an open circuit compressed air breathing apparatus (EN 137), flame retardant suit (EN469), flame retardant gloves (EN 659) and fire brigade boots (HO A29 or A30).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop the leak if there is no danger.

Wear suitable protective equipment (including personal protective equipment referred to in section 8 of the safety data sheet) to prevent contamination of skin, eyes and personal clothing. These indications are valid both for the workers and for emergency interventions.

6.2. Environmental precautions

 Cebos Color Srl 24040 Orio Sopra (BG) Via dei Dossi, 7 Tel. +39 035 265141 Fax +39 035 2651431 C.F. & P.Iva 02567630161 info@cebos.it www.ceboscolor.it	Cebos Color Srl SS 04.015 - CeboStone	Revision n. 6 Revision date 11/05/2018 Printed on 05/21/2018 Page no. 4/12
---	---	--

Prevent the product from entering sewers, surface water, groundwater.

6.3. Methods and materials for containment and cleaning up

Suck up the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used with the product, checking section 10. Absorb the remainder with inert absorbent material. Provide sufficient ventilation of the place affected by the leak. The disposal of contaminated material must be carried out in accordance with the provisions of point 13.

6.4. Reference to other sections

Any information regarding personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for Safe Handling

Handle the product after consulting all the other sections of this safety data sheet. Avoid the dispersion of the product in the environment. Do not eat, drink or smoke during use. Remove contaminated clothing and protective equipment before entering eating areas.

7.2. Conditions for safe storage, including any incompatibilities

Keep only in the original container. Keep the containers closed, in a well-ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, checking section 10.

7.3. Specific end uses

Information not available

SECTION 8. Exposure controls / personal protection

8.1. Control parameters

Normative requirements:

DEU	Deutschland	TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2017 JORF n °
BETWEEN	France	0109 du 10 mai 2012 page 8773 texte n ° 102
GBR	United Kingdom	EH40 / 2005 Workplace exposure limits
POL	Polska	ROZPORZĄDZENIE MINISTRY PRACY I POLITYKI SPOŁECZNEJ z dnia 7 czerwca 2017 r ACGIH
	TLV-ACGIH	2017

QUARTZ

Threshold limit value

Guy	State	TWA / 8h		STEL / 15min	
		mg / m3	ppm	mg / m3	ppm
MAK	DEU	0.15			
VLA	ESP	0.05			
VLEP	BETWEEN	0.1	RESPIR		
WEL	GBR	0.3			

 Cebos Color Srl 24040 Orio Sopra (BG) Via dei Dossi, 7 Tel. +39 035 265141 Fax +39 035 2651431 C.F. & P.Iva 02567630161 info@cebos.it www.ceboscolor.it	Cebos Color Srl		Revision n. 6
	SS 04.015 - CeboStone		Revision date 11/05/2018 Printed on 05/21/2018 Page no. 5/12

NDS	POL	2	INALAB
NDS	POL	0.3	RESPIR
TLV-ACGIH		0.025	

Legend:

(C) = CEILING; INALAB = Inhalable Fraction; RESPIR = Breathing Fraction; TORAC = Thoracic Fraction.

8.2. Exposure controls

Considering that the use of adequate technical measures should always take priority over personal protective equipment, ensure good ventilation in the workplace through effective local exhaust.

For the choice of personal protective equipment, if necessary, seek advice from your chemical suppliers. Personal protective equipment must bear the CE mark which certifies their compliance with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (ref. Standard EN 374).

For the final choice of the material of the work gloves it is necessary to consider: compatibility, degradation, breakage time and permeation.

In the case of preparations, the resistance of work gloves to chemical agents must be checked before use as it is not foreseeable. Gloves have a wear time that depends on the duration and method of use.

SKIN PROTECTION

Wear category I professional long-sleeved work clothes and safety footwear (ref. Directive 89/686 / EEC and standard EN ISO 20344). Wash with soap and water after removing protective clothing.

EYE PROTECTION

It is recommended to wear airtight protective goggles (ref. Standard EN 166).

RESPIRATORY PROTECTION

In case of exceeding the threshold value (eg TLV-TWA) of the substance or of one or more of the substances present in the product, it is recommended to wear a mask with a type B filter whose class (1, 2 or 3) must be chosen in relation to the limit concentration of use. (ref. standard EN 14387). If there are gases or vapors of a different nature and / or gases or vapors with particles (aerosols, fumes, mists, etc.), combined filters must be provided. The use of respiratory protection means is necessary in case the technical measures adopted are not sufficient to limit the exposure of the worker to the threshold values taken into consideration. The protection offered by the masks is however limited.

In the event that the substance in question is odorless or its olfactory threshold is higher than the relative TLV-TWA and in the event of an emergency, wear an open-circuit compressed air breathing apparatus (ref. Standard EN 137) or a self-contained breathing apparatus. outdoor air (ref. EN 138 standard). For the correct choice of the respiratory protection device, refer to the EN 529 standard.

ENVIRONMENTAL EXPOSURE CONTROLS

Emissions from manufacturing processes, including those from ventilation equipment should be controlled for compliance with environmental protection legislation.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	viscous liquid
Color	White
Odor	characteristic
Odor threshold	Unavailable
pH	8 - 9
Melting or freezing point Initial boiling point	Unavailable
Boiling range Flash point	Unavailable
	> 60 ° C

SS 04.015 - CeboStone

Evaporation rate	Unavailable
Flammability of solids and gases	Unavailable
Lower flammability limit	Unavailable
Upper flammability limit	Unavailable
explosive limit	Unavailable
Upper explosive limit	Unavailable
Vapor pressure	Unavailable
Vapor density	Unavailable
Relative density	Unavailable
Solubility	partially soluble in water
Partition coefficient: n-octanol / water:	Auto-available
ignition temperature	Unavailable
Decomposition temperature	Unavailable
Viscosity	Unavailable
Explosive properties	Unavailable
Oxidizing properties	Unavailable

9.2. Other information

VOC (Directive 2004/42 / EC):	1.10% - 11.00 g / liter
VOC (volatile carbon):	0.45% - 4.50 g / liter

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable under normal conditions of use and storage.

10.3. Possibility of hazardous reactions

In normal conditions of use and storage no dangerous reactions are foreseeable.

10.4. Conditions to avoid

None in particular. However, follow the usual precautions towards chemicals.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental toxicological data on the product itself, any health hazards of the product have been assessed on the basis of the properties of the substances contained, according to the criteria established by the reference legislation for classification. Therefore, consider the concentration of the individual dangerous substances possibly mentioned in sect. 3, to evaluate the toxicological effects deriving from exposure to the product.

 Cebos Color Srl 24040 Orio Sopra (BG) Via dei Dossi, 7 Tel. +39 035 265141 Fax +39 035 2651431 C.F. & P.Iva 02567630161 info@cebos.it www.ceboscolor.it	Cebos Color Srl	Revision n. 6 Revision date 11/05/2018 Printed on 05/21/2018 Page no. 7/12
	SS 04.015 - CeboStone	

11.1. Information on toxicological effects

Metabolism, kinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects and chronic effects from short and long term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no relevant component) LD50

(Oral) of the mixture:

Not classified (no relevant component) LD50

(Dermal) of the mixture:

Not classified (no relevant component)

SKIN CORROSION / SKIN IRRITATION

It does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / EYE IRRITATION

It does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITIZATION

May produce an allergic reaction. Contains: Reaction mass of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7]; 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1)

1,2-Benzisothiazol-3 (2H) -one 2-

octyl-2H-isothiazol-3-one

MUTAGENICITY ON GERMINAL CELLS

It does not meet the classification criteria for this hazard class

CARCINOGENICITY

It does not meet the classification criteria for this hazard class

REPRODUCTION TOXICITY

It does not meet the classification criteria for this hazard class

 © Cebos Color Srl 24040 Orio Sopra (BG) Via dei Dossi, 7 Tel. +39 035 265141 Fax +39 035 2651431 C.F. & P.Iva 02567630161 info@cebos.it www.ceboscolor.it	Cebos Color Srl	Revision n. 6 Revision date 11/05/2018 Printed on 05/21/2018 Page no. 8/12
	SS 04.015 - CeboStone	

SPECIFIC TARGET ORGAN TOXICITY (STOT) - SINGLE EXPOSURE

It does not meet the classification criteria for this hazard class

SPECIFIC TARGET ORGAN TOXICITY (STOT) - REPEATED EXPOSURE

It does not meet the classification criteria for this hazard class

DANGER IN CASE OF SUCTION

It does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

As specific data on the preparation are not available, use according to good working practices, avoiding to disperse the product in the environment. Avoid dispersing the product in the ground or water courses. Notify the competent authorities if the product has reached water courses or if it has contaminated the soil or vegetation. Take measures to minimize the effects on the aquifer.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

Information not available

12.3. Bioaccumulation potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain PBT or vPvB substances in percentage greater than 0.1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse if possible. The residues of the product as such are to be considered special non-hazardous waste.

 Cebos Color Srl 24040 Orio Sopra (BG) Via dei Dossi, 7 Tel. +39 035 265141 Fax +39 035 2651431 C.F. & P.Iva 02567630161 info@cebos.it www.ceboscolor.it	Cebos Color Srl	Revision n. 6 Revision date 11/05/2018 Printed on 05/21/2018 Page no. 9/12
	SS 04.015 - CeboStone	

Disposal must be entrusted to an authorized waste management company, in compliance with national and possibly local regulations.
CONTAMINATED PACKAGING
 Contaminated packaging must be sent for recovery or disposal in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not to be considered dangerous pursuant to the provisions in force on the transport of dangerous goods by road (ADR), by rail (RID), by sea (IMDG Code) and by air (IATA).

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard classes

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for users

Not applicable

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

 © Cebos Color Srl 24040 Orio Sopra (BG) Via dei Dossi, 7 Tel. +39 035 265141 Fax +39 035 2651431 C.F. & P.Iva 02567630161 info@cebos.it www.ceboscolor.it	Cebos Color Srl	Revision n. 6 Revision date 11/05/2018
	SS 04.015 - CeboStone	Printed on 05/21/2018 Page no. 10/12

Not relevant information

SECTION 15. Regulatory information

15.1. Health, safety and environmental legislation and regulations specific to the substance or mixture

Seveso Category - Directive 2012/18 / EC: None

Restrictions relating to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006

None

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain SVHC substances in percentage greater than 0.1%.

Substances subject to authorization (Annex XIV REACH)

None

Substances subject to export notification obligation Reg. (EC) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Sanitary checks

Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been developed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in sections 2-3 of the sheet:

Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2 Skin
Skin Corr. 1B	corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Skin Irrit. 2	Skin irritation, category 2

 Cebos Color Srl 24040 Orio Sopra (BG) Via dei Dossi, 7 Tel. +39 035 265141 Fax +39 035 2651421 C.F. & P.Iva 02567630161 info@cebos.it www.ceboscolor.it	Cebos Color Srl	Revision n. 6
	SS 04.015 - CeboStone	Revision date 11/05/2018 Printed on 05/21/2018 Page no. 11/12

Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
H301	Toxic if swallowed.
H311	Toxic in contact with the skin.
H331	Toxic if inhaled.
H302	Harmful if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure. It
H314	causes serious skin burns and serious eye injuries.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction. Very toxic
H400	to aquatic organisms.
H410	Very toxic to aquatic life with long lasting effects. Safety data sheet
EUH210	available on request.

LEGEND:

- ADR: European agreement for the transport of dangerous goods by road
- CAS NUMBER: Number of the Chemical Abstract Service
- EC50: Concentration affecting 50% of the population under test
- CE NUMBER: Identification number in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived no effect level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System for Classification and Labeling of Chemicals
- IATA DGR: Regulations for the transport of dangerous goods of the International Air Transport Association
- IC50: Concentration of immobilization of 50% of the population subject to testing
- IMDG: International maritime code for the transport of dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identification number in Annex VI of the CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal Dose 50%
- OEL: Occupational exposure level
- PBT: Persistent, bioaccumulating and toxic according to REACH
- PEC: Predicted environmental concentration
- PEL: Predictable level of exposure
- PNEC: Predicted No Effect Concentration
- REACH: EC Regulation 1907/2006
- RID: Regulations for the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that must not be exceeded during any moment of occupational exposure.
- TWA STEL: Short term exposure limit
- TWA: Weighted average exposure limit
- VOC: Volatile organic compound
- vPvB: Very persistent and very bioaccumulating according to REACH
- WGK: Water hazard class (Germany).

GENERAL BIBLIOGRAPHY:

1. Regulation (EC) 1907/2006 of the European Parliament (REACH)
2. Regulation (EC) 1272/2008 of the European Parliament (CLP)
3. Regulation (EU) 790/2009 of the European Parliament (I Atp. CLP)
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 of the European Parliament (II Atp. CLP)
6. Regulation (EU) 618/2012 of the European Parliament (III Atp. CLP)
7. Regulation (EU) 487/2013 of the European Parliament (IV Atp. CLP)
8. Regulation (EU) 944/2013 of the European Parliament (V Atp. CLP)

 Cebos Color Srl 24040 Orio Sopra (BG) Via dei Dossi, 7 Tel. +39 035 265141 Fax +39 035 2651431 C.F. & P.Iva 02567630161 info@cebos.it www.ceboscolor.it	Cebos Color Srl	Revision n. 6 Revision date 11/05/2018 Printed on 05/21/2018 Page no. 12/12
	SS 04.015 - CeboStone	

- 9. Regulation (EU) 605/2014 of the European Parliament (VI Atp. CLP)
- 10. Regulation (EU) 2015/1221 of the European Parliament (VII Atp. CLP)
- 11. Regulation (EU) 2016/918 of the European Parliament (VIII Atp. CLP)
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- NI Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA Agency website
- Database of SDS models of chemical substances - Ministry of Health and National Institute of Health

Note for the user:

The information contained in this sheet is based on the knowledge available to us at the date of the latest version. The user must ensure the suitability and completeness of the information in relation to the specific use of the product.

This document should not be construed as a guarantee of any specific property of the product.

Since the use of the product does not fall under our direct control, the user is obliged to observe the laws and regulations in force regarding hygiene and safety under his own responsibility. No responsibility is assumed for improper use.

Provide adequate training for personnel assigned to use chemical products.

Changes compared to the previous revision Changes
have been made to the following sections:

01/02/03/04/08/09/11/14/15.