Date: 01/03/2011

TECHNICAL DATA SHEET

TDS 04.010

Review n.1

Product

CEBOVEL S

Description

CEBOVEL S is a water based, acrylic, transparent, washable finish with satin look, for

interiors and exteriors.

When applied by glove or sponge to white DECORVEL, allows to create soft glazes

with distinctive chromatic shades.

CEBOVEL S is available in 1 litre, 2.5 litres and 5 litres containers.

Surface treatment of the substrate

It is applied, suitably coloured, to surfaces prepared with white DECORVEL, to reach

the desired decoration.

Colouring

CEBOVEL S can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the

same lot number.

Application

CEBOVEL S is ready-to-use and must be applied by glove or sponge in two coats: dip the chosen tool in the product and decorate the surface in uniform, circular movements

keeping the hand flat and light.

Wait until the first coat is completely dry (4 to 6 hours) and apply the second, in the

same or different colour, with the same technique.

CEBEVEL S can be applied in one coat to attain an uneven effect and a subtler colour.

Useful suggestions

VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)

Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.

CEBOVEL S contains: 35 g/l VOC

Technical characteristics

Estimated Coverage: 12 - 14 m²/litre

Appearance: liquid

Specific weight: 1.05 g/cm³

pH: 8 - 9

Resistance to washing: The product withstands ordinary cleaning maintenance. Drying time: 4-6 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct

sunshine and heat sources.

Safety warnings

CEBOVEL S does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.