



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Review n.2
Date: 15/03/2021

TECHNICAL DATA SHEET

TDS C.025

CeboWax

Description:

Water-based finish for interiors based on natural beeswax and selected binders, breathable and water-repellent.

Available packages:

1 Lt – 2,5 Lt

Coloring:

The product can be colored with the CeboColorStation tinting systems (machine or manually) or with the CeboKit universal dyes in the dosages indicated on the color charts. Colors other than those in the chart are obviously possible, by varying the required dosages and / or by mixing the dyes together. Having to prepare more packages of the same color, it is advisable to use dyes and products of same production batch.

Dilution:

From 30 to 100% in volume by water.

Mixing:

Mix the product well before and during the usage.

Suitable surfaces:

All gypsum, lime and civil substrates are suitable. Check that the surfaces are perfectly clean, dry and uniform in appearance and absorption.

Preparation of the substrates:

CeboWax can be applied on different finishes of the Cebos color line; for proper preparation of the substrate, refer to the technical data sheet of the product used to create the chosen effect.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Review n.1
Date: 06/07/2020

TECHNICAL DATA SHEET

TDS C.025

Application:

CeboWax is applied with a synthetic sponge in one or two coats.

The information on the application is contained in the videos, application sheets, folders and catalogs.

Technical features:

Drying time: 24 h

Estimated coverage: 12-14 m²/lt

Aspect: white liquid

Specific weight: 1 g/cm³

pH: 7.5 - 8.5

VOC classification (directive 2004/42 / EC):

Product Category: Decorative effect coating (I)

Maximum allowable limit (2010) for ready-to-use product 200 g/lt

CeboWax contains VOC: 3 g/l

Storage:

The product has a guaranteed shelf life of 24 months if stored in original packaging at temperatures between +5 and +35 ° C, in a well-ventilated and dry place, away from sunlight and heat sources.

Safety:

The product does not require particular environmental or personal protective measures; however it is advisable to avoid prolonged contact with the skin. In the event of eyes contact, immediately wash with clean water; if irritation occurs, consult a doctor. User information are contained in the relevant Safety Data Sheet.

This Technical Data Sheet replaces and cancels all the other Data Sheets relating to the product described, drawn up on a previous date. All the information contained in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications beyond our direct control. Our Technical Department is always at your disposal to provide further information or clarifications.