CLASSIC MALERWEISS



Washable wall paint for interiors according to DIN EN 13300

USE

Indoor walls and ceilings (ceilings, plaster, plasterboard, masonry, ...), product particularly suitable for direct applications on plasterboard surfaces.

PROPERTY'

- Washable water-based paint according to DIN EN 13300.
- Odorless.
- Easy to apply.
- Excellent hiding power.
- TÜV hygiene certificate: absence of harmful substances (heavy metals, organic compounds, plasticizers) during and after application.
- ELF quality (Emissions-und lösemittelfrei): without plasticizers, without solvents and reduced emissions (ELF labeling is attributed to paints that contain a low content of solvents or are free of them).

CHARACTERISTICS

Composition:based on synthetic resins in aqueous emulsion, pigments and selected fillers. **Density:** ca. 1,590 kg / I **Physical parameters according to EN 13300:**

- **Wet abrasion** class 3 (≥ 20 -m <70 -m to 200 cycles)

- **Hiding power** class 1 (with a yield of about 5-6 m₂/ l) (≥ 99.5%)
- **Granulometry** S.1end (<100 -m)

Emissions
 Appearance
 ELF (free from solvents, plasticizers and emissions)
 (<10 GU 85 °) (approx.1.5)

EU limit value for VOC content:Cat. A / a: 30 g / I 2010.

This product contains a maximum of 1 q / l of VOC.

Colors:White

Packaging: White: 5 and 12.5 l

Storage:keep the product in its original packaging, tightly closed and in a dry, cool and frost-free environment.

IMPLEMENTATION

Application:by brush, roller and spray (also airless: pressure: about 150 bar - nozzle: starting from 0.017 inch - filter 60 mesh - angle 40 ° - 80 °).

Dilution:20 to 40% by volume with water.

Conditions of application:application and drying must take place in temperature conditions between + 5 ° C and + 30 ° C and with relative humidity below 85%

 $\textbf{Theoretical consumption:} about \ 150 - 200 \ ml \ / \ m_2 by \ hand.$

Practical yield: about $10 - 12 \text{ m}_2/\text{ I}$ per hand. The yield may vary according to the roughness, porosity and absorption characteristics of the substrates and the application system adopted.

Drying (at 23 ° C and 50% RH):

- Overpaintable: after about 4 5 hours.
- Definitive drying: after about 2 or 3 days.

APPLICATION SYSTEMS

The application system and the preparation of the supports must be evaluated and chosen according to the current state and the conditions to which the support itself will be exposed.

Supports: the substrates must be healthy, clean, dry and free from saline efflorescence, mold, algae or fungi.





CLASSIC MALERWEISS

They must not be chalky or have parts in detachment. To clean surfaces contaminated by microorganisms use Fungimos.

Preparation of the substrates:clean the supports and consolidate the chalking ones. Repair surface defects by applying suitable products from the Polyfilla Pro line. Do not apply the product on new plasters for at least 4 weeks. In the case of patched surfaces for which it is necessary to uniform the surface texture, it is possible to apply a coat of Fassaden Putzfüller following the instructions given in the respective Technical Data Sheet.

New and highly absorbent surfaces:

- As a preparation coat, apply a coat of Classic Malerweiss diluted 50% by volume with water by brush.
- Finally, apply two coats of Classic Malerweiss diluted from 20 to 40% by volume with water depending on the application system adopted.

Surfaces already painted with washable or breathable finishes:

- Directly apply two coats of Classic Malerweiss diluted from 20 to 40% by volume with water depending on the application system adopted.

SAFETY INFORMATION

For information on the correct disposal, storage and handling of the product, please consult the relevant Safety Data Sheet.

All the technical indications contained herein are indicative. For further information, consult our Technical Assistance service.

Herbolis a trademark of: AKZO NOBEL COATINGS SPA COMMERCIAL OFFICE e ADMINISTRATIVE HEADQUARTERS: 28053 Castelletto Sopra Ticino (NO) Via Pietro Nenni, 14 Tel. 0331 916611



www.herbol.it service.clienti@akzonobel.com

The effectiveness of our products and systems is based on years of practical experience and research conducted in our laboratories. We guarantee that the quality of the work carried out with our products meets the eligibility requirements set by Akzo Nobel Coatings SpA, provided that all the instructions given by us are correctly followed and the work has been carried out according to skill and professionalism. In the event that the final result has been negatively influenced by circumstances beyond our control, any and all liability is expressly excluded and declined. The buyer is obliged to check whether the delivered products are suitable for the intended use. We reserve the right to modify the content of this document without prior notice.



