

THINNER FOR ALPHA GROND

Ideal for cleaning tools after use. Specific for Alpha Grond



Thinner for ALPHA GROND, for brush or roller applications.

PRODUCT FEATURES

Composition:	Based on a mixture of aliphatic hydrocarbons
Main properties:	<ul style="list-style-type: none"> - Specific for diluting the ALPHA GROND product - Ideal for cleaning tools after use

TECHNICAL FEATURES

Viscosity	Kinematics: 0.5 cm ² / s Kinematics (40 ° C): 0.05 cm ² / s 0.80 ± 0.02
Density (density):	kg / dm ³
Color:	Colorless
Packaging:	5 - 25 l

METHOD OF USE

storage	Store in a dry, cool and well-ventilated area, away from heat and direct sunlight. Keep away from sources of ignition. Open containers must be carefully resealed and kept straight to prevent accidental product spillage.
Blending	With Alpha Grond.
Warnings	When using DILUENTE PER ALPHA GROND to dilute ALPHA GROND, it is recommended to strictly follow the dilution instructions given in the Technical Data Sheet. Mixing in percentages other than those indicated may lead to exceeding the limits of the VOC (Volatile Organic Compounds) content provided for by Legislative Decree no. 161/2006 (Directive 2004/42 / EC) and subsequent updates.

Work in well-ventilated areas and necessarily wear suitable personal protective equipment. For more information on the correct disposal, storage and handling of the product, please consult the relevant Safety Data Sheet.

Note

All the information contained in this document is purely indicative and contains only some examples of support that do not represent the totality of the situations that in practice could be affected, therefore if it is necessary to intervene on supports not indicated or if further clarifications are necessary, we invite you to contact us and our Technical Assistance Service. Furthermore, for the correct preparation of the substrates and the application of the products, the rules for state-of-the-art installation apply, as reported in the Assovernici Technical Manual "Preserving, Protecting, Decorating with paints on the outside" and in the Sikkens "Preparation of masonry substrates" which we invite you to consult.

The effectiveness of our products and systems is based on years of practical experience and research conducted in our laboratories. We guarantee that the quality of the work carried out with our products meets the eligibility requirements set by Akzo Nobel Coatings SpA, provided that all the instructions given by us are correctly followed and the work has been carried out with skill and professionalism. In the event that the final result has been negatively influenced by circumstances beyond our control, any and all liability is expressly excluded and declined. The buyer is obliged to check whether the delivered products are suitable for the intended use.

We reserve the right to modify the content of this document without prior notice. As soon as a new version of this datasheet is available, it will no longer be valid.

relative Paints

NO)

m



is based on years of practical experience and research conducted in our laboratories. We guarantee that the quality of the work carried out with our auditors by Akzo Nobel Coatings SpA, provided that all instructions given by us are correctly followed and the work has been ity. In the event that the final result has been negatively affected by circumstances beyond our control, any and all ae declined.

Products delivered are suitable for the intended use. We reserve the right to modify the content of this document without prior notice. this data sheet will be available, this will no longer be valid.