

COPRIMAC PRIMER



F.SPECIFIC WAVE ANNEX'ANTI-STAIN AND ANTI-INICOTIN WATER

DESCRIPTION

Specific anti-stain and anti-fungal water-based primer for interiors. Isolates all types of stains (eg nicotine, halos, dry water stains, soot and smoke, felt-tip pens, etc.). The product can be applied on plaster, concrete, plasterboard.

MAIN FEATURES

- Recoatable after six hours with Coprimac, specific stain-resistant and anti-fungal finish. Quick drying.
- Excellent insulating power.
- Odorless.
- The product complies with the parameters of the European Directive 2004/42 / EC (implemented by Legislative Decree No. 161/2006) which provides for limiting the emissions of volatile organic compounds (VOCs) into the environment.

APPEARANCE

Opaque

COLORING

Semi-opaque white

TECHNICAL CHARACTERISTICS AT 20 ° C and 65% RH

Specific weight:	1.24 ± 0.05 kg / l
Theoretical yield:	6-8 m ² / l per layer according to the conditions of the substrate
Drying times:	Touch dry: 1 hour Recoatable: 6 hours (times may vary based on environmental conditions)
Storage life (in a cool and dry place):	12 months (fears frost)
Flash point (DIN 53213):	Not relevant

INSTRUCTIONS FOR USE

Mix the product thoroughly before use

Application:	Brush, roller	Spray	Airless
Recommended thinner:	Waterfall	Waterfall	Waterfall
Volume of diluent:	0-2%	0 - 5%	0 - 5%
Nozzle diameter	-	1 - 1.5 mm	0.43 - 0.48 mm
Pressure at the nozzle	-	3 - 4 atm	140 atm

06/30-2016

PPG Architectural Coatings Italy Srl -The data provided represents our best knowledge regarding the properties and uses of the product. PPG AC Italy has no control over the quality and conditions of the substrate, as well as over the multiple variables that may affect the use and application of the products. PPG AC Italy assumes no responsibility for the results.

Experimental tests are carried out at the user's risk.

UNIVER

A PPG brand

INTERVENTION CYCLES

P.REPARATION OF THE SUPPORT

Act on surfaces free from dust and poorly adhering parts. In the event of mold or algae contamination, treat the surfaces with Idrosan K Plus. On old surfaces, where necessary, smooth with a suitable mortar. Unripe plasters and patches can cause discoloration, halos and the appearance of salts.

NB In the case of already painted surfaces, check compatibility and adhesion with the proposed system.

F.ISSATIVE

Application of the fixative, depending on the type of substrate:

1 x COPRIMAC PRIMER - specific anti-stain and anti-fungal water-based primer

F.INITURA

2 x COVER

NB: do not perform applications when the temperature of the environment and of the substrate is lower than 5 ° C or higher than 30 ° C and RH higher than 85%.

SPECIFICATIONS

Painting of internal surfaces with water-based insulating primer, specifically anti-stain and anti-fungal. Specific weight of 1.24 ± 0.05 kg / l and a theoretical yield of 6-8 m²/L.

06/30-2016

PPG Architectural Coatings Italy Srl -The data provided represents our best knowledge regarding the properties and uses of the product. PPG AC Italy has no control over the quality and conditions of the substrate, as well as over the multiple variables that may affect the use and application of the products. PPG AC Italy assumes no responsibility for the results.

Experimental tests are carried out at the user's risk.

UNIVER

A PPG brand